



# Technical Data Sheet

## Quality Specification

### Palm Top 68 G

	Basis Weight	Bulk	Brightness	Breaking Length (MD)	Opacity	Roughness (TS/BS) PPS 1.0 MPa	Gloss Hunter (75°)
Dimension	[g/m <sup>2</sup> ]	[cm <sup>3</sup> /g]	[%]	[m]	[%]	[μm]	[%]
Standard	ISO 536	ISO 534	ISO 2470	ISO 1924	ISO 2471	ISO 8791-4	ISO 8254-1
	45	1.1	68	5,200	94.0	2.2	22
	48.8	1.2	68	5,500	95.0	2.2	22
	52	1.2	68	5,500	96.0	2.2	22

**Colour Specification:** **Standard**  
 ISO 5631 L\* (C/2°) 85.0  
 a\* (C/2°) 0.0  
 b\* (C/2°) 3.5

**Preconditioning:** ISO 187, 23°C, 50% relative humidity

**Tolerance:** The tolerances are within the industrial standard range.

**Certificates:** ISO 9001, ISO 14001, OHSAS 18001, ISO 50001, FSC®, PEFC, Blue Angel  
 The Eltmann mill produces paper which is EU Ecolabel compliant.

**PrePress Guidelines:** ICC Paper Profile: PSRgravureMF.icc  
 Characterisation data: PSRgravureMF\_ECI2002.txt

Issue date 01.07.2019